



Electrical

Impedance	50 ohm
Frequency Range	DC-8.5 GHz
VSWR	1.25 max
Input Avg Power	2W@ 25°C ambient, derating linearly to 0.2W at 100°C
Peak Power	200W (5 micro-sec pulse width, 0.5% duty cycle)
Direction	Bidirectional, SMA female to SMA male (other configurations available)

Attenuation(dB)	1-6	7-12	13-20	21-30	40	50	60
Accuracy(dB)	±0.4	±0.5	±0.6	±0.8	±0.8	±0.8	±0.9


Mechanical

Connector Body	Passivated stainless steel
Heat Sink	N/A
Center Contact	Gold plated beryllium copper/brass
Net Weight	Approx 6 g

Environmental

Operating Temperature	-55°C to 100°C
Storage Temperature	-55°C to 125°C
RoHS	Compliant
Temperature Coefficient	<0.0004 dB/dB/°C

Dimensions(mm)



0-12 dB: L=24
 13-30 dB: L=26.6
 40/50/60 dB: L=30

Notes

1. Customized dB values, outlines and optimal accuracy/VSWR available.

Model Description

RFHB08XXSC2

- 1.XX for dB value: 06=6dB,30=30dB
- 2.Code for connector configuration:
 A=female for two ends; B=male for two ends
 C=female for one end and male for the other.